

## TLK-270(TA270ANN-xx)

GTT TLK-270 is designed basically for 27" WXGA monitor with 1280 x 720 resolution, but also XGA mode is supported by modifying some components.

The TLK-270 is designed to provide stable/reliable touch quality as well as monitor quality by pre-integrating tough screen into open frame monitor at the monitor fab. The aluminum front cover offers lighter weight, anti-rust and beautiful looking

It offers ;

- Side mounting. Flexible mounting by customizing mounting bracket only

- Touch screens

ELO SAW(IntelliTouch) Touch, Serial Controller

Protection Glass

## RUGGED OPEN FRAME TFT-LCD MONITOR



This specification may be subject to change without notice.



### GTT Co., Ltd.

HQ : Suite 408, Unitechvil, 1141-2, Paeksok-dong, Ilsan-gu, Koyang-shi, Kyunggi-do, Korea

TEL : +82 31 903 9780, FAX : +82 31 903 9787, <http://www.gtt.co.kr>

TAIWAN : 5F-1, No. 400 Huan Pei Road, Chung Li, Taiwan, R.O.C.

TEL : +886 3 426 8255, FAX : +886 3 426 8233, <http://www.gttw.com.tw>

## SPECIFICATION

<p><b>LCD Panel</b>  Display Type  Max. Resolution  Colors  Diagonal Size  Display Area  Brightness  Contrast Ratio  Response Time  Viewing Angle</p> <p><b>Touch</b>  ELO  Protection Glass</p> <p><b>Interface</b>  VGA Input  Video Input  Touch</p>	<p>TFT LCD Panel  1280 x 720  16 Million Colors  27.0 inch  597.12mm(H) x 335.88mm(V)  550 cd/m<sup>2</sup> (Typical)  600 : 1 (Typical)  25 ms (Typical)  170°(L/R) &amp; 170°(U/D) (Typical)</p> <p>SAW Type  Anti-Reflection coating</p> <p>D-Sub15 pin  2 Composites &amp; S-video  Serial Type(RS-232)</p>	<p><b>OSD Control</b>  PC</p> <p>Video</p> <p><b>Mechanical &amp; Environmental</b>  Dimensions  Weight  Temperature</p> <p>Humidity</p> <p><b>Accessories</b>  Standard</p> <p>Optional</p> <p><b>Options</b></p>	<p>Brightness, Contrast, H-V Position, Clock, Clock phase, Color, Special, Language, Auto-config., Source, Information</p> <p>Brightness, Contrast, H/V Position, Saturation, Hue, Language, Source, Information</p> <p>684 x 422 x 76.5mm  TBD  0°C to 50°C Operating  -20°C to 60°C Storage  10%RH to 90%RH Operating  10%RH to 90%RH Storage</p> <p>15-PIN VGA cable, Power cord, AC adapter</p> <p>Touch Interface Cable,  Touch Install CD-ROM, Composite cable,  S-Video cable</p> <p>Touch  Video(Composite &amp; S-video)</p>
Part Number	Description		REMARK
TA270ANN-PG	PC + Video( 2 Composites + S-Video), Protection Glass(Material : Acryl)		
TA270ANN-ES	PC + Video( 2 Composites + S-Video), Elo SAW touch		

# DIMENSION



