



Specifications subject to change without notice.

## GTT Co., Ltd.

HQ : Suite 408, Unitechvil, 1141-2, Paeksok-dong, Ilsan-gu, Koyang-shi, Kyonggi-do, Korea  
TEL : +82 31 903 9780, FAX : +82 31 903 9787, <http://www.gtt.co.kr>

TAIWAN : 5F-1, No. 400 Huan Pei Road, Chung Li, Taiwan, R.O.C  
TEL : +886 3 426 8255, FAX : +886 3 426 8233, <http://www.gttw.com.tw>

USA : 2360 E.Devon Ave., Suite 2006, Des Plaines, IL 60018  
TEL : 847 299 5158, FAX : 847 699 1022



# Product Specifications

## TFT-LCD Panel

- Display Type	: TFT LCD Panel
- Display Area	: 15.0inch(304.1mm(H)*228.1mm(V))
- Max. Resolution	: 1024*768 - 75Hz(XGA)
- Colors	: 16,194,277 Colors
- Brightness	: 1,600cd/m2 (Typical)
- Contrast	: 350 : 1 (Typical)
- Response Time	: 23ms (Typical)
- Viewing Angle	: +60/-60 deg.(H), +40/-60 deg.(V)

## Interface

- VGA Input	: D-Sub 15pin Analog RGB
- Video Input (Option)	: 1 Composite, 1 S-Video

## Power Specifications

- DC Output	: 12Vdc
Power Consumption	: Max. 55W
- AC Input	: 100 ~ 240VAC, 50 ~ 60Hz

## OSD Control

- PC Mode	: Auto Adjust, Brightness, Contrast, H-V Position, Image Control, Color Temperature, OSD Control, Reset, Information
- Video Mode	: Brightness, Contrast, Saturation, Hue, Sharpness, Screen Size, OSD Control, Reset, Information

## Mechanical & Environmental

- Dimensions	: 332mm(W)*258mm(H)*52.6mm(D)
- Weight	: 1.92Kg
- Temperature	
Operating	: 0 ~ +50deg.C
Storage	: -20 ~ +60deg.C
- Humidity	
Operating	: 10%RH ~ 90%RH
Storage	: 10%RH ~ 90%RH

## Available Options

- Video Input	: Factory mounted (1 Composite & 1 S-Video)
---------------	--

## International Standards

TBD(UL, CE, FCC, VCCI)

# Product Dimension

