

19" OPEN FRAME



SCREEN SIZE	19 INCH
BRIGHTNESS	300 CD/M2
CONTRAST RATIO	700 : 1`
MAX RESOLUTION	SXGA (1280 X 1024)
COLORS	16.7 M colors
VIEWING ANGLE	L/R/U/D 75:75:75:60
BACKLIGHT FREQUENCY	40 KHz (H) 60KHz (V)
INPUT CONNECTORS	15P-D-SUB FOR RGB
OPTION	RCA FOR CVBS, MINI-DIN FOR S-VIDEO
	SPEAKERS
OSD CONTROLS	AUTO ADJUST , BRIGHTNESS & CONTRAST
	SIZE & POSITION, COLOR CONTROL
	LANGUAGE
POWER MANAGEMENT	VESA DPMS
PLUG & PLAY SUPPORT	DDC 1/2B
COMPATIBILITY PC	VGA TO SVGA 75HZ
POWER COMSUMPTION	0.8 WATTS (TYPICAL) 1.0 WATTS (MAX)
DPMS MODE	< 4 WATTS
POWER SUPPLY INPUT	AC 100~240V , 50 ~60 HZ
OUTPUT	DC12V 4.5A
OPERATING TEMPERATURE	0 ~50 degree
STORAGE TEMPERATURE	minus 25 ~60 degree
OPERATING HUMIDITY	0 ~ 90 %RH
STORAGE HUMIDITY	0 ~ 90 %RH
OPTIONS	TOUCH SCREEN, VESA