

### Mechanical Data

Item	Dimension	Unit
Module dimension	85.0 x 30.0 x 10.0(MAX)	mm
View area	66.0 x 16.0	mm
Active area	56.95 x 11.85	mm
Mounting hole	81.0 x 24.0	mm
Dot size	0.55 x 0.65	mm
Dot pitch	0.60x 0.70	mm
Character size	2.95 x 5.55	mm
Character pitch	3.6 x 6.3	mm

### Absolute Maximum Rating

Item	Symbol	Min	Max	Unit	Notes
Input Voltage	$V_i$	-0.3	VDD	V	
Supply Voltage For Logic	VDD-Vss	-0.3	5.3	V	

### Electronical Characteristics

em	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage For Logic	VDD-VSS	-	3.0	5.0	5.3	V
Input High Volt.	$V_{IH}$	-	0.9 VDD	-	VDD	V
Input Low Volt.	$V_{IL}$	-	GND	-	0.1VDD	V
Output High Volt.	$V_{OH}$	$I_{OH}=0.5mA$	0.8 VDD	-	VDD	V
Output Low Volt.	$V_{OL}$	$I_{OL}=0.5mA$	GND	-	0.2 VDD	V
Supply Current	$I_{DD}$	VDD=5V	-	30	-	mA

### Feature

1. 5x8 dots includes cursor
2. Built-in Controller RS0010
3. +5V power supply
4. 1/16 duty cycle
5. Interface: 6800, option 8080
6. Sunlight readable & polarizer optional

Pin No.	Symbol	Description
1	VDD	Supply Voltage for logic
2	VSS	Ground
3	NC	
4	RS	H: DATA, L: Instruction code
5	R/W	H: Read(MPU←Module) L: Write(MPU→Module)
6	E	H→L Enable signal
7	DB0	Data bit 0
8	DB1	Data bit 1
9	DB2	Data bit 2
10	DB3	Data bit 3
11	DB4	Data bit 4
12	DB5	Data bit 5
13	DB6	Data bit 6
14	DB7	Data bit 7

OLED Character type

## REC001602D OLED Character 16x2 dots

### Dimension drawing

